



Product Data Sheet

HyHeet Grease

Description: *HyHeet Grease* is a high-temperature, non-melting anti-wear grease fortified with graphite to lubricate and protect at temperatures up to 500°F. Typically used for process oven bearings, heat treat ovens and furnaces, kiln ovens, fan & blower bearings and high temperature exhaust fans.

Typical Properties:

NLGI Grade	: 2
Graphite	: 4%
Thickener	: Organo – clay gel
Penetration (@77°F)	: 275
Dropping Point	: None
Color	: Black
Shelf Life	: 1 year from ship date

Method of Use: *HyHeet Grease* is not guaranteed to be compatible with other greases- thoroughly remove old grease before using. It can be swabbed on various surfaces that require lubrication. For best lubrication, frequent relubrication is necessary at temperatures higher than 350 °F due to oxidation.

Precautions: The customary safeguards employed when storing, handling and application should be employed. To prevent contamination, container should be sealed when not in use. Please refer to Material Safety Data Sheet for proper first aid instructions.

Container Size: 14.5 oz cartridges (24 per case) or 35 lb pails



ASBURY GRAPHITE MILLS, INC.
405 Old Main Street • PO Box 144 • Asbury, New Jersey 08802
Phone: 908.537.2155 • Fax: 908.537.2908
Sales Manager: Russell Werkheiser russellw@asbury.com rev 6-1-15 www.asbury.com

For over 119 years, providing value with quality,
consistency and reliability in all we do!