



## Product Data Sheet

# Hybake Supreme

### Hot Oven Chain Lubricant

**Description:** *Hybake Supreme* is a premium high-temperature lubricant formulated with high-purity, ultra-fine graphite for maximum penetration into all moving parts. Permits ovens to be lubricated at higher temperatures, reducing costly downtime. Very simple to remix – will not settle and pack.

<b>Typical Properties:</b>	Solids Content	: 11.0%
	Graphite	: 4 micron natural graphite
	Carrier	: Water and polyalkylene glycol
	Flashpoint	: 421°F (COC)
	Weight / gallon	: 9.1 lb/gal
	Consistency	: Light Fluid
	Shelf Life	: 2 years from manufacture date

**Method of Use:** *Hybake Supreme* should be thoroughly mixed before use. Lubricant can be brushed or sprayed on chain. Do not dilute. Stir occasionally while using.

**Precautions:** Apply only at oven temperatures between 200°F and 400°F. Exhaust fans must be running and inspection doors and steam dampers must be open before and during lubrication. Shut off all burners in immediate area of application. Keep heat on in oven until all the carrier is driven off and graphite looks dry. Ventilation must be continued until all vapors are exhausted. Do not bake while vapors are still present.

Please refer to Material Safety Data Sheet for proper first aid instructions.

Note: This product is approved only as a non-food contact lubricant for food processing machinery. Please use caution to avoid food contamination.

**Container Size:** Cases of (4) 1-gallon cans, 5-gallon pails and 55 gallon drums.



**ASBURY GRAPHITE MILLS, INC.**  
405 Old Main Street • PO Box 144 • Asbury, New Jersey 08802  
Phone: 908.537.2155 • Fax: 908.537.2908  
Sales Manager: Russell Werkheiser [russellw@asbury.com](mailto:russellw@asbury.com) rev 6-1-15 [www.asbury.com](http://www.asbury.com)

For over 119 years, providing value with quality,  
consistency and reliability in all we do!